


减速比 (Ratio i)		3	4	5	6	8	10	3-6	±0.3
额定承载扭矩(Rated load torque) Nm		25	25	25	25	25	24	6-30	±0.5
最大加速力矩 (Max.acceleration torque) Nm		38	38	38	38	38	36	30-120	±0.8
急停扭矩 (Emergency stop toque) Nm		75	75	75	75	75	72	120-400	±1.2
								400-1000	±2
精密行星减速机技术参数								精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max.radial load)	700N	空载力矩20℃(No-load torque)				≤ 0.1Nm			PW65L1-i-K2-8-25- 38.1-114.7.14-M4
容许最大轴向载荷 (Max.axial load)	350N	润滑(Lubrication)				合成润滑油 (Synthetic grease)			
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度(Operation temperature)				-15℃~+90℃			
最大输入转速 (Max input speed)	6000r/min	使用寿命(Service life)				≥20000h			
噪音 (Noise)	≤ 60db	防护等级(Protection grade)				IP54		A. PW.	065.
回程间隙 (Backlash)	8arcmin			PW系列		Tel/电话: 0533-6288333 6288444			
				P2 L1		Fax/传真: 0533-6288411			
								Web/网址: www.newstart.cn	