


减速比 (Ratio i)		3	4	5	6	8	10	3-6	±0.3	
额定承载扭矩 (Rated load torque)	Nm	25	25	25	25	25	24	6-30	±0.5	
最大加速力矩 (Max. acceleration torque)	Nm	45	45	45	45	45	43.2	30-120	±0.8	
急停扭矩 (Emergency stop torque)	Nm	75	75	75	75	75	72	120-400	±1.2	
								400-1000	±2	
精密行星减速机技术参数								精密行星减速机 Precision Planetary Gear Boxes		
容许最大径向载荷 (Max. radial load)	700N	空载力矩20℃ (No-load torque)			≤ 0.1Nm				PW065L1-i-S2-8-25-38.1-□47.14-M4	
容许最大轴向载荷 (Max. axial load)	350N	润滑 (Lubrication)			合成润滑脂 (Synthetic grease)					
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)			-15℃~+90℃					
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)			≥20000h					
噪音 (Noise)	≤ 60db	防护等级 (Protection grade)			IP54			A. PW. 065.		
回程间隙 (Backlash)	8arcmin	PW系列			Tel/电话: 0533-6288333 6288444					
		P2 L1			Fax/传真: 0533-6288411					
					Web/网址: www.newstart.cn					