


减速比 (Ratio i)		12	15	16	20	25	30	32	40	50	6-30	±0.5	
额定承载扭矩(Rated load torque)		Nm		25							30-120	±0.8	
最大加速力矩 (Max.acceleration torque)		Nm		38							120-400	±1.2	
急停扭矩 (Emergency stop toque)		Nm		75							400-1000	±2	
精密行星减速机技术参数											精密行星减速机 Precision Planetary Gear Boxes		
容许最大径向载荷 (Max. radial load)		700N		空载力矩20℃ (No-load torque)				≤ 0.1Nm				 紐氏達特	
容许最大轴向载荷 (Max. axial load)		350N		润滑 (lubrication)				合成润滑脂 (Synthetic grease)					
额定输入转速 (Nominal input speed)		3000r/min		使用环境温度 (operation temperature)				-15℃~+90℃				PW65Li-i-K2-14-30- 50-70-M4	
最大输入转速 (Max input speed)		6000r/min		使用寿命 (Service life)				≥20000h					
噪音 (Noise)		≤ 60db		防护等级 (Protection grade)				IP54				A. PW. 065.	
回程间隙 (Backlash)		8arcmin				PW系列		Tel/电话: 0533-6288333 6288444					
						P2 L1		Fax/传真: 0533-6288411					
								Web/网址: www.newstart.cn					