


减速比 (Ratio i)		3	4	5	6	8	10		3-6	±0.3
额定承载扭矩 (Rated load torque)		Nm	78	78	78	78	78	68	6-30	±0.5
最大加速力矩 (Max. acceleration torque)		Nm	117	117	117	117	117	102	30-120	±0.8
急停扭矩 (Emergency stop torque)		Nm	234	234	234	234	234	204	120-400	±1.2
									400-1000	±2
精密行星减速机技术参数									精密行星减速机	
容许最大径向载荷 (Max. radial load)		1450N	空载力矩20℃ (No-load torque)			≤ 0.2Nm			Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max. axial load)		725N	润滑 (Lubrication)			合成润滑油 (Synthetic grease)				
额定输入转速 (Nominal input speed)		3000r/min	使用环境温度 (Operation temperature)			-15℃ +90℃			紐氏達特	
最大输入转速 (Max input speed)		6000r/min	使用寿命 (Service life)			≥20000h			PW90L1-i-K2-0P1	
噪音 (Noise)		≤ 63db	防护等级 (Protection grade)			IP54				
回程间隙 (Backlash)		8arcmin	PW系列		Tel/电话: 0533-6288333 6288444				A. PW. 090.	
			P2 L1		Fax/传真: 0533-6288411					
					Web/网址: www.newstart.cn					