


减速比 (Ratio i)		12	15	16	20	25	30	32	40	50	6-30	±0.5
额定承载扭矩 (Rated load torque) Nm		78									30-120	±0.8
最大加速力矩 (Max.acceleration torque) Nm		117									120-400	±1.2
急停扭矩 (Emergency stop toque) Nm		234									400-1000	±2
精密行星减速机技术参数											精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max.radial load)	1450N	空载力矩20℃ (No-load torque)				≤ 0.2Nm					 紐氏達特	
容许最大轴向载荷 (Max.axial load)	725N	润滑 (Lubrication)				合成润滑油 (Synthetic grease)						
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (operation temperature)				-15℃~+90℃						
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)				≥20000h						
噪音 (Noise)	≤ 63db	防护等级 (Protection grade)				IP54					PW90L2-i-S2-19-40-70-90-M5	
回程间隙 (Backlash)	10arcmin	PW系列				Tel/电话: 0533-6288333 6288444					A. PW. 090.	
		P2 L2				Fax/传真: 0533-6288411						
						Web/网址: www.newstart.cn						

未注线性尺寸极限偏差	
Unmarked tolerance	
0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2