


| | | | | | | | | | | |
|----------------------------------|--|-----------|-------------------------------|-----|-----|---|-----|-----|--|------|
| 减速比 (Ratio i) | | 3 | 4 | 5 | 6 | 8 | 10 | | 3-6 | ±0.3 |
| 额定承载扭矩(Rated load torque) | | Nm | 78 | 78 | 78 | 78 | 78 | 68 | 6-30 | ±0.5 |
| 最大加速力矩 (Max.acceleration torque) | | Nm | 117 | 117 | 117 | 117 | 117 | 102 | 30-120 | ±0.8 |
| | | | | | | | | | 120-400 | ±1.2 |
| 急停扭矩 (Emergency stop toque) | | Nm | 234 | 234 | 234 | 234 | 234 | 204 | 400-1000 | ±2 |
| 精密行星减速机技术参数 | | | | | | | | | 精密行星减速机 | |
| 容许最大径向载荷 (Max.radial load) | | 1450N | 空载力矩20℃ (No-load torque) | | | ≤ 0.2Nm | | | Precision Planetary Gear Boxes | |
| 容许最大轴向载荷 (Max.axial load) | | 725N | 润滑(Lubrication) | | | 合成润滑脂 (Synthetic grease) | | |  紐氏達特 | |
| 额定输入转速 (Nominal input speed) | | 3000r/min | 使用环境温度(Operation temperature) | | | -15℃~+90℃ | | | PW90L1-i-K2-16-40-80-100-M6 | |
| 最大输入转速 (Max input speed) | | 6000r/min | 使用寿命(Service life) | | | ≥20000h | | | | |
| 噪音 (Noise) | | ≤ 63db | 防护等级(Protection grade) | | | IP54 | | | | |
| 回程间隙 (Backlash) | | 8arcmin | PW系列 | | | Tel/电话: 0533-6288333 6288444 | | | A. P.W. 090. | |
| | | | P2 L1 | | | Fax/传真: 0533-6288411 Web/网址: www.newstart.cn | | | | |