


減速比 (Ratio i)	1	2					
額定承載扭矩(Rated load torque) Nm	78	68					
最大加速力矩 (Max.acceleration torque) Nm	117	102					
急停扭矩 (Emergency stop toque) Nm	234	204					

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	± 0.2
3-6	± 0.3
6-30	± 0.5
30-120	± 0.8
120-400	± 1.2
400-1000	± 2

精密行星减速机技术参数			
容许最大径向载荷 (Max. radial load)	1450N	空载力矩20℃ (No-load torque)	≤ 0.2Nm
容许最大轴向载荷 (Max. axial load)	725N	润滑 (Lubrication)	合成润滑油 (Synthetic grease)
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	≥20000h
噪音 (Noise)	≤ 63db	防护等级 (Protection grade)	IP54
回程间隙 (Backlash)	6arcmin	PW系列	Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn
		P2 L1	

	精密行星減速機 Precision Planetary Gear Boxes
	 NEWSTART® 紐氏達特
	PW90L1-i-S2-14-37- 73-口69.6-M5
A. PW.	090.