


减速比 (Ratio i)		60	64	80	100	120	125	150	160	200	6-30	±0.5	
额定承载扭矩 (Rated load torque)	Nm	78									30-120	±0.8	
最大加速力矩 (Max.acceleration torque)	Nm	117									120-400	±1.2	
急停扭矩 (Emergency stop torque)	Nm	234									400-1000	±2	
精密行星减速机技术参数											精密行星减速机		
容许最大径向载荷 (Max.radial load)	1450N	空载力矩20℃ (No-load torque)					≤ 0.2Nm					Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max.axial load)	725N	润滑 (Lubrication)					合成润滑脂 (Synthetic grease)					 NEWSTART® 纽氏達特	
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)					-15℃ +90℃						
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)					≥20000h					PW90L3-i-S2-14-37-73-□69.6-M5	
噪音 (Noise)	≤ 63db	防护等级 (Protection grade)					IP54					A. PW. 090.	
回程间隙 (Backlash)	12arcmin				PW系列		Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn						
					P2 L3								