


减速比 (Ratio i)		12	15	16	20	25	30	32	40	50	6-30	±0.5
额定承载扭矩 (Rated load torque)	Nm	78									30-120	±0.8
最大加速力矩 (Max. acceleration torque)	Nm	117									120-400	±1.2
急停扭矩 (Emergency stop torque)	Nm	234									400-1000	±2
精密行星减速机技术参数											精密行星减速机	
容许最大径向载荷 (Max. radial load)	1450N	空载力矩20℃ (No-load torque)				≤ 0.2Nm					Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max. axial load)	725N	润滑 (Lubrication)				合成润滑油 (Synthetic grease)						
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)				-15℃~+90℃					紐氏達特	
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)				≥20000h					PW90L2-i-S2-OP1	
噪音 (Noise)	≤ 63db	防护等级 (Protection grade)				IP54						
回程间隙 (Backlash)	10arcmin				PW系列		Tel/电话: 0533-6288333 6288444				A. PW. 090.	
					P2 L2		Fax/传真: 0533-6288411 Web/网址: www.newstart.cn					